

Model No.	Bearing	Voltage	Current	Input Power	Speed	Air Flow	Static Pressure	Noise
	○ Sleeve ● Ball	VDC	A	W	RPM	CFM	mm H <sub>2</sub> O	dB(A)

## Plastic Housing with Plastic Impeller



2 <sup>1/2</sup> "	60 x 60 x 25 mm	2-8/22 x 2-8/22 x 1 in							
	REC - 6025 A12 W	○	12	0.10	1.2	3950	20	3.8	27
	REC - 6025 A24 W	○	24	0.07	1.7	4200	20	3.8	27



3"	80 x 80 x 25 mm	3-1/8 x 3-1/8 x 1 in							
	REC - 8025 A12 W	○	12	0.13	1.6	2750	35	3.5	30
	REC - 8025 B12 W	●	12	0.13	1.6	2850	35	3.5	30
	REC - 8025 A24 W	○	24	0.09	2.2	2800	35	3.5	30
	REC - 8025 B24 W	●	24	0.08	1.9	3000	35	3.5	30



3 <sup>1/2</sup> "	92 x 92 x 25 mm	3-5/8 x 3-5/8 x 1 in							
	REC - 9225 A12 W	○	12	0.14	1.7	2350	46	3.5	29
	REC - 9225 A24 W	○	24	0.10	2.4	2500	46	3.5	29

## Aluminium Housing with Plastic Impeller



4"	120 x 120 x 38 mm	4-11/16 x 4-11/16 x 1-1/2 in							
	REC - 12038 A12 W	○	12	0.40	4.8	2900	105	6.8	40
	REC - 12038 B12 W	●	12	0.40	4.8	3000	110	6.8	40
	REC - 12038 A24 W	○	24	0.17	4.0	2900	105	6.8	40
	REC - 12038 B24 W	●	24	0.18	4.3	3000	110	6.8	40
	REC - 12038 B24 H W	●	24	0.32	7.7	3500	135	7.5	45
	REC - 12038 A48 W	○	48	0.13	6.2	3200	120	6.8	42
	REC - 12038 B48 W	●	48	0.13	6.2	3250	123	6.8	42
	REC - 12038 B48 H W	●	48	0.25	12	4250	164	9	52

\*H - High Speed



6"	Ø172 x 150 x 51 mm	6-3/4 x 5-7/8 x 2 in							
	REC - 17251 B24 W	●	24	0.70	16.8	3400	300	20	55
	REC - 17251 B48 W	●	48	0.35	16.8	3450	300	20	55



8"	Ø220 x 60 mm	Ø 8-21/32 x 2-3/8 in							
	REC - 22060 B24 W	●	24	1.00	24	2550	400	28	62
	REC - 22060 B48 W	●	48	0.50	24	2600	400	28	62